



EL MAYOR FABRICANTE DE
AIRE ACONDICIONADO EN EL MUNDO



SPLIT PARED INVERTER

Frío Solo - 17 SEER

220V-1F

Split PARED 17 SEER INVERTER R410A

FRÍO SOLO - MONOFÁSICO



Frío Solo

Evaporadora			GWC12ATBXA-D3DNA1A	GWC18ATDXB-D3DNA1A	GWC24ATDXE-S3DNA1A
Condensadora			GWC12ATBXA-D3DNA1A	GWC18ATDXB-D3DNA1A	GWC24ATDXE-S3DNA1A
Enfriamiento	Capacidad Nominal	Btu/h	12000	18000	24000
	Capacidad Neta	Btu/h	12000	17742	24000
	Entrada de poder	W	1160	1550	1930
Entrada de corriente		A	6.8	8.5	10.6
Min/Max. Voltaje		V	193/253	193/253	184/264
Flujo de aire		m ³ /h	620/500/410/330/270	1100/900/750/620/560	1100/900/750/620/560
Nivel de ruido		dB(A)	54/48/43/36/34	61/57/53/46/42	62/58/53/46/41
SEER			17	17	17
Alimentación Eléctrica		V/Hz/Ph	230V / 1Ph / 60Hz		220 ~ 240V / 1Ph / 50-60Hz
Serpentín			Tubería de cobre con aleta de aluminio		
Motor de Ventilador	Tipo		Cross-Flow	Cross-Flow	Cross-Flow
	Diámetro	mm	φ92×580	108×691	108×691
	RLA	A	0.24	0.24	0.24
Espaciado de Aleta		mm	2-1.4	2-1.2	2-1.2
Área		m ²	16-24	21-31	23-34
Dimensiones	Dimensiones	mm.	783 × 260 × 185	943 × 333 × 246	943 × 333 × 246
	Empaque	mm.	828 × 332 × 258	1001 × 405 × 322	1001 × 405 × 322
	Peso neto	Kg.	7.5	13	13
	Peso bruto	Kg.	9	15.5	15.5
Alimentación Eléctrica		V/Hz/Ph	230V / 1Ph / 60Hz		220 ~ 240V / 1Ph / 50-60Hz
Serpentín			Tubería de cobre con aleta de aluminio		
Compresor	Tipo		Rotativo	Rotativo	Rotativo
	Entrada de poder	W	-	962	1330
	RLA	A	4.6	4.4	6.06
Motor de Ventilador	Velocidad RPM	rpm	930	1000	900
	Entrada de poder	W	20	30	40
Min/Max. Voltage		V	193/253	193/253	184/264
Nivel de ruido		dB(A)	61	65	67
Diámetro de la tubería		mm.	φ7	φ7.94	φ5
Flujo de aire		m ³ /h	1400	2000	2800
Tipo de refrigerante		Kg.	R410A/0.54	R410A/0.7	R410A/0.9
Presión de diseño		MPa	4.3	4.3	4.3
Dimensiones	Dimensiones	mm.	710 × 450 × 293	732 × 555 × 330	873 × 555 × 376
	Empaque	mm.	764 × 330 × 525	794 × 376 × 615	951 × 431 × 620
	Peso neto	Kg.	20	24	33
	Peso bruto	Kg.	22	26.5	36
Tubería de conexión	Lado Líquido	mm	φ6	φ6	φ6
	Lado Gaseoso	mm	φ9.52	φ9.52	φ12
	Altura	m.	10	10	10
	Longitud	m.	20	25	25

AUTO

Turbo

Auto+

Auto+

EASY

● De serie ● Opcional